

# VScom 011H UPCI Low Profile

## Low Profile 1 LPT port UPCI Card

Hardware Specifications	
Ports	1 x LPT bidirectional,EPP,ECP,1284
Address	Plug and Play
Interrupts	PCI Plug and Play, only one interrupt/card
USB Interface	Universal PCI. 3.3V / 5.0V
Connectors	1x DB25 female (LPT)
Temperature	0°C - 55°C
Bracket Height	80mm Half-Height, for slimline cased PC
Operating Systems	
Windows 2000 up to 7	VScom parallel driver
Server 2000 to 2008 R2	VScom parallel driver
Windows NT 4.0	VScom parallel driver
Windows 95, 98, SE, ME	VScom parallel driver
DOS	Virtuell address driver and compatibility tools, Real DOS LPT port emulation
OS/2	Supported by COM16 driver in recent system releases
Linux	VScom LPT driver
Approvals	
EMC	FCC Class A, CE Class A
Environment	RoHS
Ordering Information	
Art. No.	4409
Product Name	VScom 011H UPCI Low Profile
Packing list	<ul style="list-style-type: none"><li>♦ VScom 011H UPCI Low Profile Card</li><li>♦ CD, English documentation</li></ul>

## Overview

The Low Profile card fits to the PCI Low-Profile specifications. As such it is usable in small cases. The parallel port allows EPP/ECP data transfer. It is best to connect high-speed printers and some other devices, such as ZIP-drives.

©2013, VSCOM. The VSCOM logo is a trademark of VS Vision Systems GmbH. Other products and brand names mentioned herein may be trademarks or registered trademarks of their respective owners. The information contained herein is subject to change without notice.

You can purchase VSCOM's products easily from a wide variety of leading technology distributors or partners.  
Please contact us to find the best ordering method for your needs.

## Connect to Success