



# VScom USB-16COMi-RM

USB to 16 RS232/422/485 ports adapter



## KEY FEATURES

- Metal case
- Rackmount and DIN-Rail mountable
- RS232/422/485 DB9 male ports
- Speed up to 500/3000 kbps
- Built-in power supply

## Overview

Serial ports on USB allow further use of existing devices, even when the computer doesn't offer serial ports.

The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.



## Specifications

Serial interface	RS232/422/485 ports
Ports	16
Speed	Up to 500 kbps RS232, up to 3000 kbps RS422/RS485
Available Modes	RS232 full duplex RS422 full duplex RS485 4 wire, full duplex RS485 2 wire, half duplex, with echo RS485 2 wire, half duplex, without echo
Signals	RS232 Tx/D, Rx/D, RTS/CTS, DTR, DSR, DCD, RI, GND RS422 Tx+/-, Rx+/-, RTS+/-, CTS+/-, GND RS485 2 wire Data+/-, GND RS485 4 wire Tx+/-, Rx+/-, GND
USB Interface	USB2.0
Power	Built-in power supply 110-240V AC 47-63 Hz, 25VA
Driver	Windows 2000 to Windows 7, Server 2000 to 2008 R2, both x86 and x64 Editions. Also Windows 98/SE/ME. Linux (Kernel 2.6.31 and up built-in)
Connectors	16 DB9 male
Dimensions	429×147×44 mm <sup>3</sup> (W×L×H); 451×152×44 mm <sup>3</sup> with DB9 connector and ears

<b>Approvals</b>	
EMC	FCC Class A, CE Class A
Environment	RoHS

## Ordering Information

Art. No	650
Product Name	VScom USB-16COMi-RM
Packing List	VScom USB-16COMi-RM Adapter; USB cable 0,9m; Power cord CD, English Documentation