



SER-485 PRO

1 port RS232 to RS422/485 Software Configurable Converter



KEY FEATURES

- Converts RS232 <=> RS422/485
- RS485 bitrate adaptive ART (Automatic Receive Transmit control)
- RS422 with Hardware handshake
- Full Software Configuration, NO Jumpers. Quick configuration for standard modes
- Flexible power 9-30V DC
- LED indicator for Power & signals
- Internal Termination and BIAS by software
- DIN-Rail mountable

Overview

The SER-485 PRO is an adapter to convert bidirectional signals from RS232 to RS422 and RS485 in industrial environments. In RS485 mode the data direction is managed by the bitrate adaptive function of ART (Automatic Receive Transmit control). ART analyzes the data in real-time, and adapts to the setup of the RS232 port.

All options and parameters of SER-485 PRO operation are configured by software, controlled via an easy-to-use menu structure. This menu is accessed via standard terminal programs. The SER-485 PRO is a NO Jumper type of device.

With SER-485 PRO often used operation modes are selected by simple DIP switches. The full versatility is controlled by the built-in software configuration menu. The behaviour of RS422 and various options of RS485 are selected by an easy-to-use menu structure.

The internal termination and BIAS (polarization) resistors allow to prepare the RS485 signals for connection to customers networks. These internal resistors are activated by relays, controlled by the configuration menu. There is no need to open the case for configuration.



Specifications

RS232	DTE/DCE selected by DIP
RS485	Automatic Receive Transmit control (ART) Baudrate adaption in real time
Line adjust	Built-in Termination and Polarization (BIAS) resistors
Operation Modes	RS422 with hardware handshake; RS485 by ART, RTS or DTR RS485 Half- and Full-Duplex; Two basic modes selected by DIP switch
Cable length	Max. 1200 m
Speed	Max. 1Mbps; Max. 250kbps with ART
Connectors	RS232 1x DB9 female RS485/RS422 1 x DB9 male plus Terminal Block (5 c-clamps)
Software Configuration	
Configuration Menu	Various parameters of signal conversion are defined via an easy-to-use menu interface, access is via standard terminal programs (Hyperterminal, miniterm, ...)
Operation Modes	RS422; RS485 by RTS; RS485 by DTR; RS485 by ART (Automatic Receive Transmit control)
ART options RS485	Transmit/Receive change as quick, average, standard

Specifications

Wiring	RS422 (4-wire) RS485 Full Duplex (4-wire) RS485 Half Duplex (2-wire) with Echo RS485 Half Duplex (2-wire) no Echo
Termination	RS422/485 line termination 120 isolated by relay, controlled via software configuration
RS485 BIAS	BIAS (polarization) by special drivers, controlled via software configuration
Power and Environment	
Power requirements	9-30V DC, 600mW
Power supply Adapter	12V DC, 500mA
Dimensions	58 x 92 x 28 mm (W×L×H)
Operating Temp	0°C - 60°C
Storage Temp	-20°C - 85°C
Case	SECC sheet metal (1mm)
Weight	150 g
Approvals	
EMC	FCC Class A, CE Class A
Environment	RoHS

Ordering Information

Art. No	417
Product Name	SER-485 PRO
Packing List	SER-485 PRO Converter, Power Supply, English Documentation
Optional Accessory	DIN-Rail mounting clamp

VScom is offering a full range of serial communication solution for industrial application fields. Currently VScom designs and manufactures technologically advanced and cost effective Ethernet to Serial, RISC-Embedded Systems, CAN Bus to Serial, USB to Serial and PCI to Serial solutions. Envisioning the rapid growth in using Ethernet in different industrial fields. VScom is presently focusing on integration of LAN and Wireless LAN technology in serial connectivity products. VScom brand products have been in the market since 1995 and are known as high quality, reliable and long life devices. More information on the products is available at www.vscom.de