

USB-COM-I PLUS

USB to 1 RS232/422/485 Port Adapter

Hardware Specifications	
Serial Interface	1 x RS232/422/485 configured by DIP switch Connector DB9 male
Speed	RS232: up to 500kbps RS422: up to 3Mbps RS485: up to 3Mbps
Available Modes	RS232 full duplex RS422 full duplex RS485 4-wire, full duplex RS485 2-wire, half duplex, with echo RS485 2-wire, half duplex, without echo
Signals	RS422: Tx+/-, Rx+/-, RTS+/-, CTS+/-, GND RS485 4-wire: Tx+/-, Rx+/-, GND RS485 2-wire: Data+/-, GND
USB Interface	USB 2.0 <ul style="list-style-type: none">Bus poweredNo external power supply
Driver	Windows 2000 to Windows 8 (x86 and x64) Windows Server 2000 to 2008 R2 (x86 and x64) Also Windows 98/SE/ME. Linux (Kernel 2.6 built-in, 2.4 available)
Approvals	
EMC Environment	FCC Class A, CE Class A RoHS
Ordering Information	
Art. No.	631
Product Name	VScom USB-COM-I PLUS
Packing list	<ul style="list-style-type: none">VScom USB-COM-I PLUS AdapterUSB cable 0,25m integrated

Overview

Industrial serial ports on USB connect RS-422 and RS485 devices, used in industrial environment. With RS-485 the data direction is controlled by the port, without further action from the software.

The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.

©2013, VSCOM. The VSCOM logo is a trademark of VS Vision Systems GmbH. Other products and brand names mentioned herein may be trademarks or registered trademarks of their respective owners. The information contained herein is subject to change without notice.

You can purchase VSCOM's products easily from a wide variety of leading technology distributors or partners. Please contact us to find the best ordering method for your needs.

Connect to Success

USB-COM-I PLUS (Art No. 631)
sales contact : sales@vsc.com.de

Datasheet Ver. : 631 PDF062013V01