



NetCom 811

8-port RS232 Serial Device Server

Hardware	
Processor	ARM 7 TDMI 50MHz
I/O controller	16C550C or compatible
Memory	8MB SDRAM, 2 MB Flash
Connector Type	RJ45 for LAN, DSUB 9 male for serial port
Interface	
LAN interface	Auto-detecting 10BaseT/100BaseTx
Protocols	TCP/IP, UDP, Telnet, DHCP, ICMP, HTTP, SNMP V1/2c/3, DNS
Serial Interface	RS232
No. of Port	8, Speed up to 460Kbps
Available Modes	RS232 full duplex
Signals	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Performance	
Speed	Up to 460Kbps
Parity	None, even, odd, space, mark
Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
IRQ	None
I/O Address	None
Operating Modes	
Driver Mode	Vscom Driver for Windows NT 4.0, 2000 up to 7, Server 2000 up to 2008 R2, both x86 and x64 Editions. The Driver creates a virtual Com port, using Vscom NetCom protocol.
TCP Raw Server	Raw data transfer over TCP/IP. Accepts multiple incoming connections.
TCP Raw Client	Raw data transfer over TCP/IP. Connects to multiple hosts or devices waiting for incoming connections.
TCP Advanced Settings	Special settings for user-defined modes
UDP Mode	Raw data transfer by UDP. The NetCom is client and server at the same time. With the timeout functionality and a configurable trigger string it can make defined UDP packets of incoming data.
Null Modem Tunnel	Connecting two NetCom used as virtual null modem cable.
IP Modem	The serial port emulates a standard modem. Operates by AT-commands, and dials to IP-Addresses instead of phone numbers. Windows "INF"-Driver provided for installation.
Print Server	The NetCom accepts print jobs, and spools them to the attached serial printer. Operates as of RFC1197, similar to the line printer daemon in Unix-systems.
Power and Environment	
Power Requirements	9 - 30V DC, 600mA @ 12V, Terminal Block
Power Supply Adapter	12V DC 1A
Operating Temp.	0°C - 60°C
Storage Temp.	-20°C - 85°C
Case	SECC sheet metal (1mm)
Dimension	167 × 99 × 43 mm ³ (W × L × H) 189 × 102 × 44 mm ³ with DB9 connectors and ears
Weight	700g
Special Features	
Installation	Configuration utility automatically finds NetCom devices in the network
Operating Mode	Automatic mode switching between Driver and TCP RAW mode. With TCP Advanced settings it is possible to configure the NetCom for using it in multiple modes, so it decides automatically which mode should be used.
Configuration	Configuration over Driver Panels, NetCom Manager, WEB Browser, serial console, Telnet, SNMP
SNMP	Special Vscom MIB included
ART	No
DNS	Domain Name Server support
Firewall	Special precautions for Firewall environments
Firmware	Firmware update over WEB Browser, Telnet, ComPort
LEDs	LEDs for Power, Tx, Rx, LAN Link, LAN Speed

8-port RS232 Serial Device Server

Security	
Password Access	Every capabilities of configuration use the same password including SNMP V3
Approvals	
EMC Environment	FCC Class A, CE Class A RoHS
Ordering Information	
Art. No.	670
Product Name	VScom NetCom 811
Packing list	<ul style="list-style-type: none"> ◆ VScom NetCom 811 Adapter ◆ Power supply adapter 12V, 1A ◆ CD-ROM with Driver and configuration software ◆ Printed Quick Installation Guide
Optional Accessories	<ul style="list-style-type: none"> ◆ DK 35A (Art No.662) - DIN-Rail mounting kit ◆ 9PF-9PF (Art No.661) - Serial Adapter : Null-Modem adapter, change male to female

Overview

NetCom 811 is an industrial-strength network-based serial device server for connecting eight RS232 device like CNC, PLC, weighting scale, scanner and other devices directly to the 10/100Mbps Ethernet network running TCP/IP.

In addition to allowing serial devices to get networked, any host (PC Server or Workstation) without network access can also access remote serial device via adding NetCom devices to the existing serial port. NetCom 811 can be configured over Driver Panels, WEB Browser, serial Port, Telnet, SNMP and serves as a transparent serial channel without platform and distance limitation.

©2013, VSCOM. The VSCOM logo is a trademark of VS Vision Systems GmbH. Other products and brand names mentioned herein may be trademarks or registered trademarks of their respective owners. The information contained herein is subject to change without notice.

You can purchase VSCOM's products easily from a wide variety of leading technology distributors or partners. Please contact us to find the best ordering method for your needs.



Connect to Success

www.vscom.de
sales contact : sales@vscom.de